



40MHz, 532nm AO Frequency Shifter

I-FS040-1.5S2C-3-GH83

A compact Acousto-Optic Frequency Shifter featuring low power 100mW 40MHz supply requirement and high diffraction efficiency, this device is ideal for use in heterodyne interferometric systems, particularly laser Doppler velocimetry and has been designed to facilitate double pass configuration.

In addition to the specifications indicated, we also offer alternative wavelengths, RF frequencies, active apertures & a wide range of custom housing configurations. We also offer full custom design & manufacturing, enabling our customers to achieve the perfect solution.

Our scientists and engineers are available to assist in selecting the most appropriate Acousto-Optic device and RF driver for your application.

Please contact our sales team for further information.

Key Features:

- □ 40MHz □ 532nm
- ☐ High efficiency
- Tellurium Dioxide

Applications:

- Industrial:
 - Laser Doppler Vibrometry
 - Laser Doppler Velocimetry
 - 3D laser scanning



General Specifications

Device: AO Frequency shifter Interaction material: Tellurium Dioxide

RF Drive Frequency: 40MHz Operational wavelength: 532nm Reflectivity per surface: < 0.2%

Minimum optical aperture: 4 x 2.0 mm (horizontal and vertical)

Active aperture: 1.5mm (vertical)
Transmission: > 95% @ 532nm
Maximum diffraction efficiency: > 90% @ 532nm

Polarisation of input beam:

Linear and horizontal with respect housing

Linear and orthogonal to input and zero

order beams

Zero to 1st order polarisation extinction ratio: > 100:1

Output Configuration:

Diffracted & undiffracted Symmetrical to the left and right of the straight through

direction ± 0.5°

Separation (0 to Diffracted-order): 2° RF Drive Power: $\leq 80 \text{mW}$ Input Impedance: 50Ω

RF connector: SMA Bulkhead Jack

Ordering Code

Explanation: I-FS040-1.5S2C-3-GH83 (Frequency Shifter, 40MHz, 1.5mm active aperture, shear mode, Tellurium Dioxide, 532nm, SMA male, GH83 housing).

I - F S 0 4 0 - 1 . 5 S 2 C - 3 - G H 8 3



